

# THINNER 120

## special thinner for polyurathane coatings

Special thinner for all two- pack polyurethane coatings of our company.

- ▶ POLYGLOSS
- ▶ POOLGLOSS
- ▶ POLYFLOOR
- ▶ ANTISKID
- ▶ MONOTRETEN
- ▶ UNI PRIMER
- ▶ X-RUST

### TOOLS

roller, brush or airless spray gun

### TECHNICAL CHARACTERISTICS

TYPE	MIXTURE OF SOLVENTS	
SPECIFIC GRAVITY	TRANSPARENT	0.85 ±0,05gr/cm <sup>3</sup>
FLASH POINT	25 °C	

### REGULATION 2004/42/CE

Does not fall into the categories stipulated in Regulation 2004/42/EC.

### PACKAGING

- ▶ Available in containers of 500ml and 1L.



### STORAGE

2 years if unopened and stored under normal storage conditions. Once opened, seal well and store in a closed place at room temperature between 5-25°C. Keep tightly closed after application for future use. Store in a cool place. Protect against freeze and direct sunlight.

### CLEAN-UP / DISPOSAL

Always handle empty containers and product carefully. Do not pour leftover product down the drain. Strictly follow local, regional, national regulations and legislation on the disposal of products and empty containers.

### HEALTH & SAFETY

Read carefully the safety instructions on the label. For more information, consult the Safety Data Sheet.

