

# TSUNAMI<sup>2</sup> Mk2

## Aerator Pumps

A breath of fresh air



NEW PRODUCT

### Tsunami Aerator Mk2

Keep your bait and fish alive with the new Tsunami Aerator Mk2. Our leading fish-friendly technology is even easier to install and service, cutting costs for both suppliers and end users.

#### Flexible Installation

- Both 90 and straight inlets and outlets

#### Full Backwards Compatibility

- With previous Tsunami models

#### Faster, Smarter Installation

- With no sealant or tools required



#### Inlet Thread Types

- Seacock**
  - 3/4-14 NPT
  - 1-11-1/2 NPT
- Straight 1-1/2"**
  - 3/4-14 NPSM
  - 1-3/8-12 UNF
- Straight 3-1/2"**
  - 3/4-14 NPSM
  - 1-3/8-12 UNF
- Angled 4"**
  - 3/4-14 NPSM
  - 1-3/8-12 UNF

#### Inlet Types

- Straight
- Angled

#### Primary Outlet Sizes

- 500 & 800 - 3/4",
- 1200 - 1-1/8"

#### Secondary Outlet Sizes

- 1/2", 3/4" & 1-1/8"

#### Number of Outlets

- Two

## Tsunami Aerators Mk2

Model	Inlet Style	Inlet Length & Diameter	Application	OEM Part #	OEM Outlet Straight	OEM Outlet 90°	Part #	Aftermarket Outlets Included
<b>Tsunami Aerator Mk2 Pumps</b>								
T500	Straight	3-1/2" L x 3/4"	Thru-Hull	5640-1	AS5605SS-1 (3/4" barb)	AS5605ES-1 (3/4" barb)	5640-4	Straight & Elbow, 3/4" included
		1-1/2" L x 3/4"	Thru-Hull	5641-1	or	or	—	
		7/8" L x 3/4"	Seacock	5643-1	AS5605QLS-1 (3/4" Qwik-Lok™)	AS5605QLE-1 (3/4" Qwik-Lok™)	5643-4	
	Elbow	3-1/2" L x 3/4"	Thru-Hull	5644-1			5644-4	
T800	Straight	3-1/2" L x 3/4"	Thru-Hull	5650-1	AS5605SS-1 (3/4" barb)	AS5605ES-1 (3/4" barb)	5650-4	
		1-1/2" L x 3/4"	Thru-Hull	5651-1	or	or	—	
		7/8" L x 3/4"	Seacock	5653-1	AS5605QLS-1 (3/4" Qwik-Lok™)	AS5605QLE-1 (3/4" Qwik-Lok™)	5653-4	
	Elbow	3-1/2" L x 3/4"	Thru-Hull	5654-1			5654-4	
T1200	Straight	3-1/2" L x 1-1/8"	Thru-Hull	5660-1	AS5612SS-1 (1-1/8" barb)	AS5612ES-1 (1-1/8" barb)	5660-4	Straight & Elbow, 1-1/8" included
		1-1/2" L x 1-1/8"	Thru-Hull	5661-1	or	or	—	
		7/8" L x 1"	Seacock	5663-1	AS5605QLS-1 (3/4" Qwik-Lok™)	AS5605QLE-1 (3/4" Qwik-Lok™)	5663-4	
	Elbow	3-1/2" L x 1-1/8"	Thru-Hull	5664-1			5664-4	
<b>Tsunami Mk2 Aerator Replacement Motor Cartridges</b>								
T500				—	—	—	5620-6	
T800				—	—	—	5622-6	
T1200				—	—	—	5624-6	

## Accessories—Aftermarket

Model	564X / T500	565X / T800	566X / T1200	564X / T500	565X / T800	566X / T1200
Inlet Hose Connector	3899	3899	3902	3899	3899	3902
Inlet Hose ID	3/4"	3/4"	1-1/8"	3/4"	3/4"	1-1/8"
Thru Hull	66547	66547	66549	66547	66547	66549
Primary Outlet Connectors	AK5605S-7 (3/4" - 0° & 90°)	AK5605S-7 (3/4" - 0° & 90°)	AK5612S-7 (1-1/8" - 0° & 90°)	AS5605ES-1 (3/4" - 90°) AS5605SS-1 (3/4" - 90°)	AS5605ES-1 (3/4" - 90°) AS5605SS-1 (3/4" - 90°)	AS5612ES-1 (1-1/8" - 90°) AS5612SS-1 (1-1/8" - 0°)
Secondary Outlet Connectors	AK5670-7 (1/2" - 0° & 90°, 3/4" - 0° & 90°, 1-1/8" - 0° & 90°)	AK5670-7 (1/2" - 0° & 90°, 3/4" - 0° & 90°, 1-1/8" - 0° & 90°)	AK5670-7 (1/2" - 0° & 90°, 3/4" - 0° & 90°, 1-1/8" - 0° & 90°)	AS5671E-1 (1/2" - 90°) AS5672E-1 (3/4" - 90°) AS5673E-1 (1-1/8" - 90°)	AS5671E-1 (1/2" - 90°) AS5672E-1 (3/4" - 90°) AS5673E-1 (1-1/8" - 90°)	AS5671S-1 (1/2" - 0°) AS5672S-1 (3/4" - 0°) AS5673S-1 (1-1/8" - 0°)
Remote Brackets	4122-3	4122-3	4121-3	4122-1	4122-1	4121-1
Inlet Strainers	3885-3 (Plastic) 3886-3 (Plastic incl. Thru-hull) 4232-7 (SS)	3885-3 (Plastic) 3886-3 (Plastic incl. Thru-hull) 4232-7 (SS)		3885-3 (Plastic) 3886-3 (Plastic incl. Thru-hull) 4232-7 (SS)	3885-3 (Plastic) 3886-3 (Plastic incl. Thru-hull) 4232-7 (SS)	
Spray Heads	4118A5 (Spray Bar) 4125-7 (Adjustable)	4118A5 (Spray Bar) 4125-7 (Adjustable)		4118A5 (Spray Bar) 4125-7 (Adjustable)	4118A5 (Spray Bar) 4125-7 (Adjustable)	
Replacement Motor Cartridge	5620-6	5622-6	5624-6	5620-6	5622-6	5624-6

Please note that all Primary Outlets do fit all pump models with outlet threads. Attwood recommends the standard outlet types to ensure maximum efficiency of the pump.

## Specifications

Model	Hole Saw Size	Amp Fuse	Outlet Diameter	ABYC Specifications 13.6-volts DC (GPH=Gallons Per Hour)			ISO Specifications 12.0-volts DC (LPH=Liters Per Hour)		
				0 ft. Head GPH/amps	3.3 ft. Head GPH/amps	6.7 ft. Head GPH/amps	0m Head LPH/amps	1m Head LPH/amps	Max Head (ft. @ 13.6V/m@12V)
564X / T500	1-1/8"	3A	3/4" barb	507 / 1.6	319 / 1.7	192 / 1.6	1764 / 1.4	1182 / 1.4	10.4 / 2.6
565X / T800	1-1/8"	4A	3/4" barb	793 / 3	498 / 2.9	371 / 2.9	2694 / 2.5	2142 / 2.5	17.4 / 4.2
566X / T1200	1-3/8"	5A	1-1/8" barb	1143 / 3.9	748 / 3.9	527 / 3.8	3912 / 3.3	3282 / 3.3	14.8 / 3.8