
Product name	:	MoTip Silicone Spray
Article number	:	090107
Supplier / Producer	:	MOTIP DUPLI B.V. Wolframweg 2 NL-8471 XC WOLVEGA Telephone number +31 561 – 69 44 00 Telefax number +31 561 – 69 44 31

Product description

High quality silicone spray to lubricate and protect plastic or rubber parts.

Applications

Door rubbers	Creaking plastic parts
Dashboards	Bumpers
Sunshine roofs	Rails (caravan, blinds)
Sliding doors	Saw blades
Remove agents for moulds	

Product characteristics

Excellent adhesion
Water-repellent
Prevents freezing and drying out of rubber parts
Prevents creaking and squeaking of plastic parts
Outstanding mechanical and thermal stability
Resistant to weather influences
Resistant to weak acids and bases
Directed jetspray

Physical and Chemical Characteristics

Contents	:	500 ml
Basis	:	Polydimethylsiloxaan
VOC-content	:	Approximately 88% w/w
Colour	:	Transparent
Scent	:	Characteristic
Relative density at 20°C	:	0,72 g/ml
Vapour pressure at 20°C	:	3 to 4 bar
Refractive Index at 25°C	:	1,403
Disruptive strength	:	14 kv/mm at a temperature of 20°C
Resistance	:	4×10^{15} Ohm/cm
Temperature resistant	:	-50°C to +200°C
pH-value	:	Neutral



Usage

Before use, carefully read the directions on the packaging and act accordingly.

The aerosol should have room temperature.
Best processing temperature 5 to 30°C.
Before use, shake the aerosol.

Apply silicone spray in a thin layer. Optimum lubrication is obtained after evaporation of the solvent (approximately 1 minute).